



DAKAFLASH

A Fully Adhesive Reinforced Flashing

FREQUENTLY ASKED QUESTIONS

Primary Product Uses:

DAKAFLASH; primary flashing to replace traditional lead flashing in most applications, predominantly used on residential tile roofs but can also be used on metal and polycarbonate. Dakaflash has the same aluminium mesh insert as Wakaflex and can stretch up to 30% on 2 dimensional profiles.

Contents

Q: Where can I buy Dakaflash?

Q: Is Dakaflash cheaper than lead flashing?

Q: Can you use Dakaflash to fix existing faulty/leaking lead flashing?

Q: Where can Dakaflash be installed?

Q: Can Silicone & Sikaflex be used on Dakaflash?

Q: Can Dakaflash be installed on corrugated roof profiles?

Q: Do you need any specialist tools to install Dakaflash?

Q: Can Dakaflash be used as Dampcourse?

Q: Can Dakaflash be painted?

Q: Can Dakaflash be installed if you have a water tank for potable water?

Q: How do I install Dakaflash?

Q: How is the installation of Dakaflash different from lead?

Q: Can Dakaflash just be stuck up against the brickwork, rendered wall or fascia?

Q: Can Dakaflash be used on Metal & Polycarbonate roofs?

Q: Can Dakaflash be installed on a property prone to bushfire?

Q: Where is Dakaflash Made and how long has it been on the market?

Q: How long is Dakaflash guaranteed for?

Q: What is Dakaflash made of and what are it's properties?

Q: Where can I buy Dakaflash?

A: Dakaflash can be purchased directly from Web Industrial.

We conduct regular market research and know our prices to be extremely competitive in the WA market. If at any time you find a better price, we encourage you to contact us via our website, email or phone. **We will happily price match and beat wherever possible, upon presentation of a current invoice or quotation.**

Volume Discounts

Generous discounts are offered for bulk orders. Our loyal customers receive discounted pricing based upon volume and frequency of orders.

Q: Is Dakaflash cheaper than lead flashing?

A: Dakaflash is considerably cheaper than lead flashing. Remember that all of our flashings come in a 5m roll. Lead is usually comes in 3m roll. On average Dakaflash is \$130 for a 300mm x 5m roll and lead is \$155 for a 300mm x 3m Roll at trade prices.

Q: Can you use Dakaflash to fix existing faulty/leaking lead flashing?

Yes. The easiest way is to lift up your existing lead and install Dakaflash directly underneath it, you can install the Dakaflash in full 5m lengths. Then dress down the existing lead over the Dakaflash as an over-flashing. You can trim the existing lead back if you want a smaller over-flashing. If you completely remove the lead you will need to chase the Dakaflash back into brickwork, use an over-flashing of some kind or go underneath the fascia.

Q: Where can Dakaflash be installed?

A: Dakaflash can be installed in any situation where traditional lead flashings are installed. Abutments, Dutch Gables, Step-Flashings & Chimneys, Sky Lights, Penetration flashings. Dakaflash can also be used to line normal gutters and box gutters. Dakaflash can also be used to flash HVAC installations, and is suitable for the maintenance of existing flashings. Dakaflash can be used to go over tile, metal or polycarbonate roofing sheets with leakage problems.

Q: Can Silicone & Sikaflex be used on Dakaflash?

A: We recommend Sikaflex Pro should be used with Wakaflex. Roofer's silicon is not recommended.

Q: Can Dakaflash be installed on corrugated roof profiles?

A: Yes Dakaflash is compatible with metal & polycarbonate roofing materials and can be easily stretched to provide a tight fit on corrugated profiles and other extreme profiles of metal and polycarbonate roof profiles.

Q: Do you need any specialist tools to install Dakaflash?

A: No tools are required, Dakaflash can be installed and dressed down by hand. The easy way to dress Dakaflash is by using both thumbs. How much you dress the main body of Dakaflash to the roof profile is up to the installer, however the butyl adhesive must be dressed down to the roof to create adhesion and a watertight seal. Dakaflash can stretch up to 60% in length so it can be dressed around 360 degrees, but it doesn't have to be stretched when installed.

Q: Can Dakaflash be used as Dampcourse?

A: Yes. Dakaflash is fully tested to AS/NZS 2904:1995 Damp Proof Course & Flashings.

Q: Can Dakaflash be painted?

A: Yes. An outdoor acrylic paint should be used such as Watty1 Solagard or Dulux Weather Shield.

Q: Can Dakaflash be installed if you have a water tank for potable water?

A: Dakaflash is non-toxic but it's not currently tested to AS/NZS 4020:2005: Products in contact with drinking water. If you wish to collect drinking water from your roof for drinking Wakaflex should be installed as it complies with AS/NZS 4020:2005. Wakaflex is also available from Web Industrial.

Q: How do I install Dakaflash?

A: In the same way as you would install lead flashing. Dakaflash is installed horizontally for abutments, gables and pitches roofs where there is a fascia or cladding on the second storey level. If Dakaflash is to be installed on a pitched roof on a brick second storey then it must be built in as Step-Flashing or it can be chased into the brickwork or it can be mechanically over-flashed with a thin strip of metal. Please check your local building codes. All local builders & plumbers should understand how it should be installed. (For more installation details see question below)

Q: How is the installation of Dakaflash different from lead?

A: Dakaflash can be installed in full 5m lengths whereas Lead (20kg for external flashings) must be installed in sheets no longer than 1.5m with 150mm over-lap when joining sheets. Dakaflash only requires a 50mm butyl to butyl join which forms a watertight seal. 20kg lead flashing is very heavy and difficult to move around the roof but Wakaflex is very light, it's only 2.5kg for a 300mm x 5m roll so it's much easier to install. Dakaflash is also available in 3 colours, Grey, Black and Terracotta.

Q: Can Dakaflash just be stuck up against the brickwork, rendered wall or facia?

A: No. Dakaflash must always be built in, chased in or over-flashed to ensure the warranty is valid. A mechanical over-flashing such as a metal strip can be used in some instances. Please check with your local building codes. Dakaflash is not covered by the warranty if it's just adhered to external brickwork or facia.

Q: Can Dakaflash be used on Metal & Polycarbonate roofs?

A: Yes. Dakaflash does not react with any metal or plastic roofing materials. Although Dakaflash is designed to replace lead flashing on tiled roofs it can also be used for metal & polycarbonate, however it must still be built-in, chased-in or over-flashed. Dakaflash can be placed onto an open patch of metal roof as a patch but it is not covered by the guarantee in this application.

Q: Can Dakaflash be installed on a property prone to bushfire?

Dakaflash has not currently been tested to a BAL level. Therefore Wakaflex is recommended for fire prone areas as it has been tested to BAL29 (Bushfire Attack Level) which means it can be installed on properties in areas categorised BAL29 and below as long as the installation follows CSIRO's recommendations which is the correct installation with no air space behind the Wakaflex flashing. Please contact us for additional information if required. Wakaflex is available from Web Industrial.

Q: Where is Dakaflash made?

A: Dakaflash is made in Germany, Europe.

Q: How long is Dakaflash guaranteed for?

A: Dakaflash comes with a 10 year guarantee as long as it's installed according to the installation instructions. The guarantee does not cover incorrect installation, accidental damage or acts of god.

Q: What is Dakaflash made of and what's its properties?

A: Dakaflash is a creped Aluminium top sheet with a 100% butyl adhesive backing. It has a 2 part protective silicon backing paper to keep it clean until

installation. Dakaflash has good chemical stability and is resistant to heat, ozone, acid and is UV resistant. It's also extremely weather resistance as its air & water vapour impermeable. The creped sheet allows Dakaflash to expand up to 60% along the length of the roll meaning it can create a watertight profile around extreme roof profiles and even flash around 360 degrees such as penetration pipes.

KEY DAKAFLASH FACTS

- Dakaflash can be purchased from Web Industrial, available 7 days.
- It can stretch up to 30% in length.
- It has a creped Aluminium top sheet.
- It has a 100% butyl adhesive backing.
- It can be installed on bull noses & curved roofs.
- It can be dressed down onto 3 dimensional profiles.
- It is suitable for skylights, roof vents, heating & cooling units and any normal penetration.
- It is completely non-toxic.
- It can be installed on tile, metal, polycarbonate & slate roofs.
- It does not react with other metals.
- It can be installed in complete 5m lengths.
- It can be joined by over-lapping by 100mm with the underlying roll turned up by 20cm.
- It comes in 300mm & 450mm widths all in 5m length rolls.
- Available in Black, Lead Grey & Terracotta colour.
- Dakaflash is completely watertight & airtight.
- Dakaflash has a 10 year guarantee if installed correctly.