

MAKE THE SMART CHOICE WITH



# SMARTFORM

FLEXIBLE ROOF FLASHING AND ALL PURPOSE REPAIR TAPE



- Multi-functional
- Highly flexible with up to 60% stretch
- Quick & easy to use
- Up to 50% quicker than lead to install
- Fully adhesive backing
- Non-toxic & lightweight



See our full lead free flashing range at  
[www.evobuild.com.au](http://www.evobuild.com.au)





**With its 60% stretchability and 100% butyl self-adhesive backing, Smartform is the smart choice for lead-free roof flashing and all-purpose weatherproofing repairs**

Smartform has a coated creped aluminium foil surface and butyl self-adhesive backing that is perfect for creating a watertight solution, even in difficult to seal penetrations.

Compatible with both metal and tile roofing, Smartform is ideal for new build houses and general roofing maintenance. It can be used for wall connections, dormers, chimney abutments, box gutter repairs, as well as many other applications.

Provided surfaces are dry and dust-free, Smartform can be installed quickly and easily due to the ability of the material to stretch and fit different structures.

**FEATURES**

- High quality self-adhesive butyl solution
- Up to 50% quicker to install than lead
- Rapidly installed water-tight solution
- Superior workability (stretchable)
- Light-weight and easy to carry on the roof
- UV resistant
- Available in 3 colours and 3 sizes

**APPLICATIONS**

- Wall connections, dormers and chimney abutments
- Corners of sky lights
- Flashing repairs
- New build houses and many repair situations
- Water tank repairs
- And weather-proofing in many other situations

**INSTALLATION**

1. Measure and cut the appropriate length of flashing. Fold & crease to the required dimensions down the length of the flashing relevant to the angle of installation
2. Peel back the top section of the protective backing paper
3. Apply the exposed top section to the area of application with hands before peeling back the second section of the released paper
4. Remove the bottom section of protective backing paper and dress with hands to the desired profile

**SPECIFICATIONS**

- Complies with AS/NZS 4020:2005 'Products for use in contact with drinking water' and AS/NZS 2904:1995 'Damp course flashing'
- Aluminium composite top sheet with butyl adhesive backing
- 2 piece protective backing for easy installation
- Suitable for temperature ranges from -25C up to 90C
- 100% Watertight
- Stretchability up to approx. 60%
- Non-toxic, lightweight & easy to install
- 10 Year Warranty\*
- Smartform should not be built into brickwork and should be over-flashed at all times

\*For full warranty information go to [www.evo.build.com.au/smartform.html](http://www.evo.build.com.au/smartform.html)

**COLOURS AND SIZES**

Smartform is available in 5m rolls in 3 colours and 3 sizes:

Colour/Width	200mm	300mm	450mm
Lead Grey			
Terracotta			
Black			



Distributed by Evo Building Products  
 PO Box 96 Matraville NSW 2036  
 Tel: 02 9666 1069 Fax: 02 9666 1870  
[www.evobuild.com.au](http://www.evobuild.com.au)